

PRODUCT DATA SHEET FOR INDUSTRIAL INSULATION

Product Name	CLIMCOVER Lamella Mat / ML 3
Manufacturer	Saint Gobain Isover G+H AG
Certification number	011-6V023
Certification body	DIN CERTCO
Designation Code	MW EN 14303-T4-ST(+)-260-MV2
Labeling	Keymark + VDI-mark
Form of supply	Lamella Mat
European Standard	DIN EN 14303:2013-04
Thermal Conductivity (W/mK)	
Maximum service temperature	260
Minimum service temperature	
Thickness Range (mm)	020-120
Reaction to Fire (Euroclass)	A1
Temperature 1	50
Thermal conductivity 1	0.044
Temperature 2	100
Thermal conductivity 2	0.056
Temperature 3	150
Thermal conductivity 3	0.072
Temperature 4	200
Thermal conductivity 4	0.091
Temperature 5	
Thermal conductivity 5	
Temperature 6	
Thermal conductivity 6	
Temperature 7	
Thermal conductivity 7	
Temperature 8	
Thermal conductivity 8	
Temperature 9	
Thermal conductivity 9	
Temperature 10	
Thermal conductivity 10	
Air-flow resistance	
Water vapor diffusion resistance	MV2
Content of water-soluble chloride ions	
Water absorption	